



"NPT" (EACH END)

No.	DESCRIPTION	MATERIAL
1	STEM	LOW LEAD BRASS ALLOY
2	O-RING	EPDM ASTM D2000
3	BALL	LOW LEAD BRASS ALLOY
4	GASKET - SEAL	NITRILE ASTM D2000
5	BODY	CAST LOW LEAD BRASS ALLOY
6	O-RING	EPDM ASTM D2000
7	END PIECE	CAST LOW LEAD BRASS ALLOY
8	CAP	CAST BRASS ASTM B62 ALLOY C83600
9	SOLID PIN	AISI 303 STAINLESS STEEL
10	LEVER HANDLE	CAST BRASS ASTM B62 ALLOY C83600
11	MACH. SCREW	AISI 304 STAINLESS STEEL
12	HEX LOCKNUT	TYPE 18-8 STAINLESS STEEL

VALVE SIZE	A	NPT SIZE
3/4"	3-1/16"	3/4"
1"	3-31/32"	1"
1-1/2"	4-1/8"	1-1/2"
2"	4-15/16"	2"

PART NUMBER
E1905
JJ-MRKTG

FILEPATH: PRDD-ENG\JJ\SUBMITTALS\E1905

						DRFTR JGarvin 12/1/09	JAMES JONES CO.		
						UNLESS OTHERWISE NOTED			THIRD ANGLE PROJECTION
						SURFACE PREPARATION: BREAK CORNER(S) ---- .000 SURFACE FINISH -- XX RMS			REF. No. SCALE
						TOLERANCE(S): LINEAR ----- ± .000 ANGULAR ----- ± 0°00'			
						BY DATE			
						STK No:			
						MAT'L:			
						DESCR.	PART NUMBER		
						BALL TYPE CURB VALVE w/ HANDLE LOW LEAD BRASS (FIP - BOTH ENDS)	E1905		
REV	ECR	DESCRIPTION	DATE	BY	CHKR				