



No.	DESCRIPTION	MATERIAL
1	STEM	CAST BRASS ASTM B505 ALLOY C83600
2	O-RING	EPDM ASTM D2000
3	BALL	CAST BRASS ASTM B505 ALLOY C83600
4	GASKET - SEAL	NITRILE ASTM D2000
5	BODY	CAST BRASS ASTM B62 ALLOY C83600
6	O-RING	EPDM ASTM D2000
7	END PIECE	CAST BRASS ASTM B62 ALLOY C83600
8	SOLID PIN	AISI 303 STAINLEES STEEL
9	CAP	CAST BRASS ASTM B62 ALLOY C83600
10	HANDLE	CAST BRASS ASTM B62 ALLOY C83600
11	MACH SCREW	AISI 304 STAINLEES STEEL
12	HEX LOCKNUT	AISI 18-8 STAINLEES STEEL

VALVE SIZE	A	NPT SIZE
3/4"	3-1/16"	3/4"
1"	3-31/32"	1"
2"	4-15/16"	2"

"NPT" (EACH END)

A

FILEPATH: PRDD-ENG\JAMESJONES\SUBMITTALS\J1900WH

					DRFTR JGarvin 6/8/10	JAMES JONES CO.	UNLESS OTHERWISE NOTED SURFACE PREPARATION: BREAK CORNER(S) ---- .000 SURFACE FINISH -- XX RMS TOLERANCE(S): LINEAR ----- ± .000 ANGULAR ----- ± 0°00'	THIRD ANGLE PROJECTION	
					CHKR			REF. No. SCALE	
					ENGR				
					MGR				
					BY	DATE			
					STK No:				
					MAT'L:				
					DESCR.		BALL TYPE CURB VALVE LEVER HANDLE(FIP - BOTH ENDS)		PART NUMBER J1900WH
REV	ECR	DESCRIPTION	DATE	BY	CHKR				

PART NUMBER
J1900WH
 JJ-MRKTG