



PARTS LIST:

ID	PART NAME	MATERIAL
1	HYDRANT HEAD BODY	ASTM B584 ALLOY C89833 OR C87600
2	HYDRANT SPOOL	ASTM B584 ALLOY C89833 OR C87600
3	DOME CAP	ASTM B584 ALLOY C89833 OR C87600
4	REMOVEABLE NOZZLE	ASTM B584 ALLOY C89836 OR C89833
5	HOSE CAPS	SEE OPTIONS
6	HYDRANT STEM	SILICON BRONZE ASTM B584 C87600
7	STEM LOCKNUT	BRASS ASTM B584 ALLOY C89833
8	BEVELED HYDRANT DISC	BUNA-N
9	HYDRANT DISC LOCKNUT	BRASS ASTM B584 ALLOY C89833
10	STEM INSERT	BRASS ASTM B584 ALLOY C89833
11	PENT NUT	SILICON BRONZE ASTM B584 C87600
12	PENT NUT RETAINER	BRASS ASTM B62 UNS C83600
13	HYDRANT DISC HOLDER	BRASS ASTM B584 ALLOY C89836
14	NOZZLE GASKET	NEOPRENE

PRODUCT FEATURES:

	FEATURE DESCRIPTION
1	INDIVIDUAL STEM OPERATION
2	PRODUCT RATED UP TO 200 PSI; HYDROSTATICALLY TESTED AT 400 PSI
3	LOW ZINC SILICON BRONZE STEMS
4	HEAVY DUTY DISC HOLDER
5	O-RING CONSTRUCTION IN STEM INSERT
6	NOZZLE SIZES: 2-1/2" TOP; 2-1/2", 4", OR 4-1/2" BOTTOM
7	HOSE CAPS: BRONZE OR PLASTIC
8	PENT NUTS: 1-1/8", 1-1/2", 1-3/4"
9	REMOVEABLE NOZZLES AND DOME CAP ARE OPTIONAL
10	STANDARD 8-HOLE AND 6-HOLE FLANGE BOLT PATTERNS
11	VARIOUS OUTSIDE FINISHES AVAILABLE
12	
13	
14	

Approvals:

Date: