



MANUFACTURED IN COMPLIANCE WITH AMERICAN  
WATER WORKS ASSOCIATION, WET-BARREL FIRE  
HYDRANT STANDARD, AWWA C-503

PARTS LIST:

ID	PART NAME	MATERIAL
1	HYDRANT HEAD	ASTM B584 ALLOY C89833
2	HOSE CAPS	PLASTIC OR BRONZE
3	HYDRANT STEM	ASTM B584 ALLOY C87600
4	STEM LOCKNUT	ASTM B584 ALLOY C89833
5	BEVELED HYDRANT DISC	BUNA-N
6	HYDRANT DISC LOCKNUT	ASTM B584 ALLOY C89833
7	STEM INSERT	ASTM B584 ALLOY C89833
8	PENT NUT	ASTM B584 ALLOY C87600
9	PENT NUT RETAINER	ASTM B62 ALLOY C83600
10	HYDRANT DISC HOLDER	ASTM B584 ALLOY C89836
11	NOZZLE INSERT	ASTM B584 ALLOY C89836
12		
13		
14		

PRODUCT FEATURES:

	FEATURE DESCRIPTION
1	INDIVIDUAL STEM OPERATION
2	LIMITED NUMBER OF INTERNAL PARTS
3	PRODUCT RATED UP TO 200 PSI; HYDROSTATICALLY TESTED AT 400 PSI
4	AVAILABLE IN A VARIETY OF BOLT HOLE PATTERNS
5	LOW ZINC SILICON BRONZE STEMS
6	HEAVY DUTY DISC HOLDER
7	O-RING CONSTRUCTION IN STEM INSERT
8	PENT NUTS SIZES AVAILABLE; 1-1/8", 1-1/2", 1-3/4"
9	PLASTIC CAPS AVAILABLE
10	10 YEAR LIMITED WARRANTY
11	VARIOUS OUTSIDE FINISHES AVAILABLE
12	NOZZLE THREADS CONFORM TO NFPA 1963, NH/NST
13	
14	

Approvals:

Date: