



350 PSI RATING



350 PSI RATING

PARTS LIST:

PRODUCT FEATURES:

ID	PART NAME	MATERIAL	FEATURE DESCRIPTION
1	HYDRANT BODY	DUCTILE IRON GR. 65-45-12 DR 70-50-05	1 MEETS OR EXCEEDS ANSI/AWWA C503
2	NOZZLE INSERTS	BRASS ASTM B584 ALLOY C89833	2 INDIVIDUAL STEM OPERATION
3	HOSE CAPS	DUCTILE IRON GR. 65-45-12 DR 70-50-05	3 LIMITED NUMBER OF INTERNAL PARTS
4	HYDRANT STEM	SILICON BRONZE ASTM B584 C87600	4 NOZZLE THREADS CONFORM TO NFPA 1963, NH/NST
5	STEM LOCKNUT	BRASS ASTM B584 ALLOY C89833	5 REMOVABLE NOZZLE DESIGN
6	BEVELED HYDRANT DISC	BUNA-N	6 AVAILABLE IN A VARIETY OF BOLT HOLE PATTERNS
7	HYDRANT DISC LOCKNUT	BRASS ASTM B584 ALLOY C89833	7 LOW ZINC SILICON BRONZE STEMS
8	STEM INSERT	BRASS ASTM B584 ALLOY C89833	8 HEAVY DUTY DISC HOLDER
9	PENT NUT	BRASS ASTM B584-UNS C87600	9 PRODUCT RATED UP TO 350 PSI; HYDROSTATICALLY TESTED AT 700 PSI
10	PENT NUT RETAINER	COPPER ALLOY UNS C83600	10 O-RING CONSTRUCTION IN STEM INSERT
11	HYDRANT DISC HOLDER	BRASS ASTM B584 ALLOY C89836	11 EPOXY COATED INTERIOR MEETS AWWA C550 AND NSF 61
12	NOZZLE GASKET	NEOPRENE	12 PLASTIC CAPS AVAILABLE
13	O-RINGS	NITRILE RUBBER	13 10 YEAR LIMITED WARRANTY
14	DOME CAP	DUCTILE IRON GR. 65-45-12 DR 70-50-05	14 5" STORZ PUMPER NOZZLE AVAILABLE
15	DOME CAP O-RING	NITRILE RUBBER	

Approvals:

Date: